

universal busbar support (01 500)



Description

Article

Part No.: 01 500

universal busbar support

3-pole with additional external screw holes

for busbars 12, 15, 20, 25, 30 x 5, 10

for busbars 12, 15, 20, 25, 30 x 5, 10

System

60Classic

Product group 06

Subgroup 09

pack size 10

EAN 4021267015008

Advantages of the product

With additional external screw holes

can also be used as centre support

eCl@ss 6.1 27400607

eCl@ss 7.1 27400607

ETIM 4.0 EC001166

ETIM 5.0 EC001166

Approvals

Standards

IEC 61439-1:2011

Approvals

Germanischer Lloyd



Type number: S610

CCC approval: no certification required

Product data

Electrical data

Rated voltage (IEC) AC: 690
V

Power dissipation:

The power dissipation at a typical load of 80% of the rated current results to 0 W.
(The power dissipation for operation with rated current would be 0 W.)

Rated surge voltage U_{imp} : 8 kV
max. permitted voltage (IEC) AC: 1000
V
max. permitted voltage (IEC) DC: 1500
V

Mechanical data

W x H x D: 20 x 215 x 50

Weight: 13.7 kg/100

Poles: 3-pole

for busbars: 12, 15, 20, 25, 30 x 5, 10

Material properties

Main temperature stability 125°C,


body: self-extinguishing in acc. to UL 94,

creepage resistance CTI 600,

halogen-free

Screws: screw +/- (PZ2), galvanized, chromized

Accessories



01 573

end cover

for busbar supports 01 484, 01 495, 01 500, 01 508 and 01 603