



# LEUCHTMITTELÜBERSICHT

## LEUCHSTOFFLAMPEN RINGFORM Ø 16 mm

BEZEICHNUNG		LEISTUNG	SOCKEL	RA	FARBTEMPERATUR	LICHTSTROM	BESTELLNUMMER
ZVEI/LBS	OSRAM						
	T16R FC	22 W	2GX13	1B	3000 °K	1800 lm	L15W528489
	T16R FC	22 W	2GX13	1B	2700 °K	1800 lm	L15W646237
	T16R FC	22 W	2GX13	1B	4000 °K	1800 lm	L15W528465
	T16R FC	22 W	2GX13	1B	6500 °K	1700 lm	L15W528441
	T16R FC	40 W	2GX13	1B	3000 °K	3200 lm	L15W528540
	T16R FC	40 W	2GX13	1B	2700 °K	3200 lm	L15W646251
	T16R FC	40 W	2GX13	1B	4000 °K	3200 lm	L15W528526
	T16R FC	40 W	2GX13	1B	6500 °K	3000 lm	L15W528502

## LEUCHSTOFFLAMPEN STABFORM Ø 16 mm

BEZEICHNUNG		LEISTUNG	SOCKEL	RA	FARBTEMPERATUR	LICHTSTROM	BESTELLNUMMER
ZVEI/LBS	OSRAM						
	T16 FH	14 W	G5	1B	3000 °K	1200 lm	L15W464824
	T16 FH	14 W	G5	1B	2700 °K	1200 lm	L15W645933
	T16 FH	14 W	G5	1B	4000 °K	1200 lm	L15W464688
	T16 FH	14 W	G5	1B	6500 °K	1100 lm	L15W464848
	T16 FH	21 W	G5	1B	3000 °K	1900 lm	L15W464800
	T16 FH	21 W	G5	1B	2700 °K	1900 lm	L15W645971
	T16 FH	21 W	G5	1B	4000 °K	1900 lm	L15W464701
	T16 FH	21 W	G5	1B	6500 °K	1750 lm	L15W464626
	T16 FH	28 W	G5	1B	3000 °K	2600 lm	L15W464787
	T16 FH	28 W	G5	1B	2700 °K	2600 lm	L15W646015
	T16 FH	28 W	G5	1B	4000 °K	2600 lm	L15W464725
	T16 FH	28 W	G5	1B	6500 °K	2400 lm	L15W464640
	T16 FH	35 W	G5	1B	3000 °K	3300 lm	L15W464763
	T16 FH	35 W	G5	1B	2700 °K	3300 lm	L15W646053
	T16 FH	35 W	G5	1B	4000 °K	3300 lm	L15W464749
	T16 FH	35 W	G5	1B	6500 °K	3050 lm	L15W464664
	T16 FQ	24 W	G5	1B	3000 °K	1750 lm	L15W453491
	T16 FQ	24 W	G5	1B	2700 °K	1750 lm	L15W646091
	T16 FQ	24 W	G5	1B	4000 °K	1750 lm	L15W453477
	T16 FQ	24 W	G5	1B	6500 °K	1600 lm	L15W453453
	T16 FQ	39 W	G5	1B	3000 °K	3100 lm	L15W453552
	T16 FQ	39 W	G5	1B	2700 °K	3100 lm	L15W646138
	T16 FQ	39 W	G5	1B	4000 °K	3100 lm	L15W453538
	T16 FQ	39 W	G5	1B	6500 °K	2850 lm	L15W453514
	T16 FQ	49 W	G5	1B	3000 °K	4300 lm	L15W657158
	T16 FQ	49 W	G5	1B	2700 °K	4300 lm	L15W657172
	T16 FQ	49 W	G5	1B	4000 °K	4300 lm	L15W657134
	T16 FQ	54 W	G5	1B	3000 °K	4450 lm	L15W453415
	T16 FQ	54 W	G5	1B	2700 °K	4450 lm	L15W646176
	T16 FQ	54 W	G5	1B	4000 °K	4450 lm	L15W453392
	T16 FQ	54 W	G5	1B	6500 °K	4050 lm	L15W453378
	T16 FQ	80 W	G5	1B	3000 °K	6150 lm	L15W515137
	T16 FQ	80 W	G5	1B	2700 °K	6150 lm	L15W646213
	T16 FQ	80 W	G5	1B	4000 °K	6150 lm	L15W515151
	T16 FQ	80 W	G5	1B	6500 °K	5700 lm	L15W515113